



Material Compatibility

Product: **Optisal Plus**
Material number: **00-245-000**
Concentration: **3.0 %**

The product has been tested according to SOP 04.02.012 and SOP 04.02.027 to be suitable with the following materials.

Recommended for the use on

Metals	<input checked="" type="checkbox"/> Stainless steel V2A <input checked="" type="checkbox"/> Stainless steel V4A	
Surface	<input checked="" type="checkbox"/> Polyurethane (PU) <input checked="" type="checkbox"/> Concrete	<input type="checkbox"/> Synthetic leather <input type="checkbox"/> Linoleum
Plastics	<input checked="" type="checkbox"/> Polyoxymethylene (POM) <input checked="" type="checkbox"/> Acrylonitrile - Butadiene - Styrene (ABS)	<input checked="" type="checkbox"/> Polymethylmethacrylate (PMMA)
Elastomers	<input checked="" type="checkbox"/> Silicone <input type="checkbox"/> Neoprene (CR)	<input type="checkbox"/> Ethylene-Propylene-Dienemonomer (EPDM)

Recommended usage

As surfaces may vary in quality the product suitability should be checked by testing first on a small inconspicuous area.
To ensure materials compatibility please do not exceed recommended concentration, contact time and temperature.

Not recommended for the use on

- | | |
|--|---|
| <input type="checkbox"/> Aluminum
<input type="checkbox"/> Brass
<input type="checkbox"/> Copper | <input type="checkbox"/> Polyamide (PA)
<input type="checkbox"/> Polycarbonate (PC)
<input type="checkbox"/> Polyethylene terephthalate (PET) |
|--|---|

Date: 0.7.19


Jens Nielsen, Head of R&D