

Material Compatibility

19.10.2015

Product: **Cleanisept**
Mat. No.: **00-204-000**

The product has been tested according to SOP 04.02.012 and SOP 04.02.027 to be suitable with the following materials.

Recommended for the use on

Metals:	■ Stainless Steel V2A	■ Aluminum anodized
	■ Stainless Steel V4A	■ Brass chromed
	■ Aluminum	
Surfaces:	■ Polyvinyl chloride (PVC)	■ Synthetic leather
	■ Wood floor	■ Linoleum
	■ Glass	■ Caoutchouc
	■ Tiles	
Plastics:	■ Polystyrene (PS)	■ Polysulphone (PSU)
	■ Polyphenylenoxide (PPO)	■ Polyester (PES)
	■ Teflon (PTFE)	■ Polyvinylchloride (PVC)
	■ Polyethylene (PE, HDPE)	■ Polymethyl methacrylate (PMMA)
	■ Polyoxymethylene (POM)	■ Polyamide (PA)
	■ Polyetherketon (PEEK)	
Elastomers:	■ Nitril- Butadiene rubber (NBR)	■ Ethylene- Propylene- Dienmonomer (EPDM)
	■ Silicone	■ Caoutchouc
	■ Polychloroprene (Neopren)	■ Polyurethane (PUR)
	■ Fluore Elastomere (Viton)	
	■ Santoprene (TPE-V)	

■ Recommended usage

■ As surfaces may vary in quality the product suitability should be checked by testing first on a small inconspicuous area.
To ensure materials compatibility please do not exceed recommended concentration, contact time and temperature.

Not recommended for the use on

- | | |
|----------------|---|
| ■ Copper | ■ Polycarbonate (PC) |
| ■ Brass | ■ Acrylonitrile-butadiene-styrene (ABS) |
| ■ Latex rubber | |

Dr. Erik Brückner

Head of R&D Disinfection, **Dr. Schumacher GmbH**

